



MSME / ISO CERTIFIED COMPANY

Contact No.: 9450802091, 9511152052

E-mail: info@poojaindustriesup.com

web: www.poojaindustriesup.com

D-2 Adhar Khera Kursi Road, Lucknow - 226022

Product Catalogues & Technical Specification



1. E-Cart for Garbage With or Without Tipping Facility:-



- Capacity of Container – 200 Ltr.
- Motor Rating – 1kw. Min.
- Battery – 4 Nos (Reputed Make)
- Hydraulic System operated through Powerpack.
- Structure of Container made of 25*25mm MS Pipe.
- Wall made of 1.6mm Thick MS Sheet.
- Hydraulic Jack Capacity – 5 Ton.
- Whole System mounted on Suitable Channel Section.
- Use to carry Dry & Wet Waste separately.



2. Double Wheel Barrow or Hand Cart :



- Material – Mild Steel Sheet of 14/16 gauge
- Frame – Mild Steel Angle of 35*35*5mm
- Axle – 25mm Solid MS Rod
- Wheel – 12inch Rubber Cushioned/MS Flat/ T-Iron
- Handle – 35*35*5mm MS Angle.
- Size – 3*2*1 Feet
- Wheel run on Bush Shaft or Bearing.



3. Hydraulic Tractor Trailer or Trolley



- Dimension 10*6*2 (In feet) Normally
- Hydraulic System operated through PTO of Tractor attached with.
- Mild Steel Sheet 10 Sqr gauge (On Wall sides of Trolley).
- Mild Steel Sheet 8 Sqr Gauge (On Bottom).
- Main Frame 200*50 mm thick Heavy-Channel.
- Other Structure 75*40*5 mm Channel.
- Wheel 02 Wheel.
- Wheel Size 7.50*16 or 900*20.
- Hydraulic Cylinder Capacity – 15 Ton.
- Axel 90 mm.



4. Manual Tractor Trailer or 04 wheeler Trolley :



- Dimension – 10*6*2 (In feet) Normally
- Mild Steel Sheet 10 Sqrgauge (On Wall sides of Trolley).
- Mild Steel Sheet 8 Sqr Gauge (On Bottom).
- Main Frame 165*50 mm thick Heavy-Channel.
- Other Structure 75*40*5 mm Channel.
- Wheel 04 Wheel.
- Wheel Size 7.50*16 or 900*20.
- Wheel Brand – JK/BIRLA/MRF/CEAT as Required.
- Axel – 72 mm 02 Axel.



5. Mobile Toilet :



- Type - 04/06/08/10 Seater Mobile Toilet.
- Main Frame - 75x40 Heavy Channel.
- Wall made of MS/SS/PUFF/ACP/PVC/Fiber Sheet.
- Roof made of MS/SS/PUFF/ACP / PVC/Fiber /CorrigatedSheet.
- Toilet Sheet - Fiber/SS/CeremicSheet.
- Bottom Structure made of MS/SS/FiberSheet.
- 02 Washbasin fitted outside of cabin.
- Mounted on 02 / 04 wheeler suitable chassis.
- All required amenities fitted in toilet as per required.
- Cabin Size - 6x3x3 in feet.



6. Single / Double Barrel Fogging Machine :



- Type – Thermal Aerosol Pulse Jet Fogging Machine.
- Starting Type – Electrical & Manual.
- Power – 56cc./27.5 kw
- Carburettor Structure – Self Suction Carburettor.
- Fuel Tank Capacity – 2.5 Ltr .
- Chemical Tank Capacity – 8.2 Ltr
- Fuel Consumption – 2.5 Ltr
- Engine Form – Piston Type.
- Frame Material – Stainless Steel



7. Single/Twin Bin Dumper Placer :-



- Use to carry garbage bins automatic and offload them.
- Whole system operated hydraulically through PTO/Powerpack.
- Bins Capacity – 0.9 to 4.5Qbc (Depends on Vehicle)
- Bottom Structure made of heavy duty MS Channel.
- Main Platform made of 3mm thick MS Sheet.
- Stabilizer fitted 02 Nos. on rear side of Chassis for stability.
- Above Side booms made by 6 - 8 mm thick MS Pipe.
- MS Heavy chain & Hooks use to attached bins with system.
- Its also having Single/Double bin lifting system hydraulically.



8. Backholoader / Mini Tractor Loader :-



- Minimum Engine Capacity of Tractor – 55Hp
- Operated Through Tractor's PTO.
- Max. Working Height – 10'5" (Backho)
- Max. Load Over Height - 7" (Backho)
- Max. Dipping Depth – 7'6" (Backho)
- Bucket Rotation Power – 180 Degree. (Backho)
- Bucket Volume – 0.12m³
- Depth of Bucket – 56" (Front)
- Bucket Opening Distance – 3"



9. Cattle Catcher :

- We offer Cattle Catcher Vehicle which is well designed for animal pickups & transportation.
- It come in Trolley based & Vehicle based body.



**CATTLE CATCHER
ON TROLLEY**

**CATTLE CATCHER
ON VEHICLE**



10. Water Tanker on Single Axle Trailer :



- Capacity - 2.0 kl to 4.0 kl.
- Main frame made of 150*65*5mm MS Channel.
- Tank made by 10 mm thick MS/SS Heavy Sheet.
- Wheels – 02/04 Nos. Rear Side.
- Axel – 80 Mm. Minimum.
- A Ladder and 2 Open cap provided on Top.
- It comes with Tap, Shower & Ball Valve for extra pipe connection.
- Used through tochen with tractor.



11. Refuse Compactor :-



- Vehicle Type – Heavy Motor Vehicle
- GVW Required – 16120 KG Min.
- Control–Electrically Hydraulic Control.
- Discharge Model – Horizontal Ejection.
- Operation Mode – Vehicle's PTO
- PTO Type- Vehicle Auxiliary.
- Max Pressure of Pump – 240 Bar
- Panel Thickness – 4mm MS
- Container Capacity – 7-14m³



12. TryCycle or Rickshaw :-



- Vehicle Type- Heavy Motor Vehicle
- Underground Bin Capacity -1100Ltr.
- Capacity of Platform- Min 04 Bin
- Underground Container Volume-1.1cum
- Container Material-SS -304
- Top Finish of cap platform – Chequered GI Sheet.
- Power Management L-Iron Replaceable Battery
- Ejection Mechanism–Telescopic Hydraulic Ram
- Regulation of Ejection – Hydraulic Control Unit.



Deals in Tractor

◆ Escort Tractor Ltd. ◆ Sonalika Tractors Ltd. ◆ M&M Ltd. ◆ Swaraj Tractor Ltd. ◆ Eicher Tractors

